

V230

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3086 mm (121.5") height to hinge pin
- ✓ 1707 mm (67.2") machine width - less bucket
- ✓ 3497 kg (7,710 lbs.) operating weight

IMPERIAL

CAPACITIES	Operating Capacity At 50% Tipping Load	2300 lb
	Operating Weight	7749 lb
	Unladen weight	6982 lb
	Tipping capacity	4600 lb
WEIGHT AND DIMENSIONS	Wheelbase	43 in
	Overall Operating Height - Fully Raised	161 in
	Height to Hinge Pin - Fully Raised	122 in
	Overall Height to top of ROPS	81 in
	Dump angle at full height	42 °
	Dump height	91 in
	Overall length with bucket	141 in
	Dump reach - Full height	33 in
	Rollback Angle at Full Height	92 °
	Seat to ground height	39 in
	Overall width less bucket	67 in
	Ground clearance	8 in
	Overall length - Less Bucket	110 in
	Clearance Radius - Front with Bucket	85 in
PERFORMANCES	Travel speed (unladen)	8 mph
	Travel Speed with Two-Speed Option - Maximum	12 mph
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine nom	Tier 4
	Max. torque / Engine rotation	217 ft/lbs / 1800 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine power (Hp / kW)	71.50 Hp / 52.33 kW
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
Starter	3 kW	
HYDRAULICS	Standard flow - Auxiliary hydraulics	23 US gpm
	Auxiliary Hydraulic Pressure	3475 PSI
	High-Flow Auxiliary Hydraulics - Option	30 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3325 PSI
TANK CAPACITIES	Fuel	28 US gal
	Hydraulic tank capacity	6 US gal
	Displacement	0.87 US gal
	Cooling liquid	5 US gal

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls

OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- LED front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera
- Sliding Side Windows



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT